



Ted M. Zobeck
USDA/Agricultural Research Service
Lubbock, Texas 79401
tzobeck@mail.csrl.ars.usda.gov

Research has shown that the distribution of aggregates on the soil surface is generally log-normal and can be adequately described by the geometric mean diameter and the geometric standard deviation (Gardner, 1956). We measure DASD by dry sieving a 5 kg air-dried sample of surface soil in a rotary sieve (Fig 1., Chepil, 1942). We then regress the natural logarithm of sieve diameter on the normal probability of the fraction of soil passing that diameter (Fig 2). The normal probability is determined using the PROBIT function of SAS¹ software (SAS, 1990). The geometric mean diameter is the antilog of the sieve size at 50% passing. The geometric standard deviation is described by the equation (Allen, 1981):

GMD/Diameter at 84% passing [1]



References

Allen, T. 1981. Particle Size Measurement. 3rd Ed., London., Chapman and Hall.,

Chepil, W. S. 1942. Measurement of wind erosion by dry sieving procedure *Sci. Agric.* 23:154-160.

Chepil, W. S. 1951. Properties of soil which influence wind erosion: IV. State of aggregate status *Soil Sci.* 72:387-401.

Gardner, W. R. 1956. Representation of soil aggregate-size distribution by a logarithmic-normal distribution *Soil Sci. Soc. Am. Proc.* 20:151-153.

SAS Institute. 1990. SAS/STAT User's Guide, Version 6, Fourth Ed., Cary, NC, SAS Inst.